



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

B23D 79/02, 13/00, 27/14

(11) International Publication Number:

WO 91/01839

(43) International Publication Date:

21 February 1991 (21.02.91)

(21) International Application Number:

PCT/GB90/01147

A1

(22) International Filing Date:

25 July 1990 (25.07.90)

(30) Priority data:

8918174.7 9000677.6

9 August 1989 (09.08.89)

GB 12 January 1990 (12.01.90)

Published

With international search report.

patent), SE (European patent), SU, US.

(81) Designated States: AT (European patent), BE (European

patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), IT (Europ

pean patent), JP, LU (European patent), NL (European


(71)(72) Applicants and Inventors: BARRACLOUGH, Keith, Sylvester [GB/GB]; Old Court Barn, West Mudford, Yeovil, Somerset BA21 5TJ (GB). CAREY, Ian [GB/GB]; The Dairy House, Charlton Horethorne, Sherborne, Dorth Control of the Contr set DT9 4NX (GB).

(74) Agents: DUNLOP, Brian, Kenneth, Charles et al.; Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB).

(54) Title: CUTTING TOOL

(57) Abstract

A cutting tool (10) has a part-elliptical symmetrical cutting edge (11). A holder (14) may be provided for allowing rotation of the tool (10) about an axis passing through its point of symmetry to provide a range of cutting radii. The application also includes the methods and apparatus utilising such tools.



BEST AVAILABLE COPY

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	мс	Monaco
ΑU	Australia	FI	Finland .	MG	Madagascar .
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Fasso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD.	Sudan
CF	Central African Republic	KP	Democratic People's Republic	SE	Sweden
CC.	Congo		of Korea	SN	Senegal
CH	Switzerland	KR	Republic of Korea	รบ	Soviet Union
CM	Cameroon	LI	Liechtenstein	αT	Chad ·
DE	Germany, Federal Republic of	LK	Sri Lanka	TC	Togo
DK	Denmark	LU	Luxembourg	US	United States of America

15

20

25

Cutting Tool

This invention relates to cutting tools and in particular, but not exclusively, to cutting tools for use in the removal of weld upset on the continuous weld produced during welded tube manufacture.

Current practice is to remove such scarf by drawing the tube under a cutting tool which has a radiused cutting edge which is intended to correspond closely with the outer radius of the tube so that a clean cut is achieved. The tools are, however, quite expensive and it is impractical to keep or manufacture a full set of tools dimensioned to cover the full range of tube sizes produced in a normal plant. Thus in practice, what occurs is that a compromise is reached between cost and efficiency of removal, with the result that the scarf removal does not match the radius of the tube or the surface of the tube is marked by the tool.

Proposals have been made to try to overcome this problem by rotating the tool, but because of the geometry of the radius the result is simply that the ends of the cutting tool dig in to the tube.

From one aspect the invention consists in a tool for removing burrs, scarf or the like from a circular cross-section body, the tool having a part elliptical symmetrical cutting edge.

Preferably, the cutting edge is constituted by less than a quarter of an ellipse so that the short axis of the

15

20

25

ellipse extends through the centre line of the cutting edge. In this arrangement the centre line portion of the cutting edge produces a radius for one size of body and a range of other radiuses can be achieved by rotating the cutting edge about an axis extending through its centre line because when viewed along that axis the cutting edge will tend to a radius as it is rotated. Thus instead of digging in to the tube, as is the case with a radiused cutting edge, the elliptical cutting edge tool provides an infinitely variable range of radii about the central value determined by the radius of the centre line portion when it is substantially coplanar with the cross-section of the tube.

Thus the cutting edge is preferably dimensioned such that it will conform with a range of body radii dependant of the rotational position of the cutting edge to the cross-sectional plane of the body.

When used in this way the cutting tool must be so formed as to provide the top rake and clearance angles required to allow for efficient cutting.

Grooves may be incorporated into the surface of the tool to provide control of the material being removed and to reduce any twisting moment on the material being scarfed.

It will be appreciated that the cutting tool may be in the form of a removable insert or may be constituted by an integral tool.

From another aspect the invention consists in apparatus for removing burrs, scarf or the like from a circular cross-section body comprising a tool having a part elliptical

10

20

symmetrical cutting edge, means for supporting the body and the tool for relative movement for causing the cutting edge to cut over a longitudinal track on the body and means for mounting the tool for rotation about an axis orthogonal to the axis of the body, when located on the support means, and passing through the point of symmetry of the cutting edge.

In a preferred embodiment the tool is mounted in a tool holder having means for adjusting the rotational position of the tool, the angle of cut and/or the longitudinal position of the tool.

The invention also consists in a method of removing scarf from a continuously formed tube by means of a cutting tool having a part-elliptical cutting edge and tube processed by this method.

Although the invention has been defined above it is to be understood it includes any inventive combination of the features set out above or in the following description.

The invention may be performed in various ways and a specific embodiment will now be described, by way of example, with reference to the accompanying drawings, in which:-

Figure 1a illustrates a cutting tool held at an angle of twist to a tube as viewed from above;

Figure 1b is an end view of the arrangement of Figure 25 1;

Figure 1c is a side view of that arrangement;

Figure 2a is a front view of the cutting tool of Figure 1 mounted in a tool holder;

15

20

25

Figure 2b is a side view of that tool holder;

Figures 3a to 3c correspond to Figures 1a to 1c but with the tool inclined;

Figures 4a and b correspond to Figures 2a and 2b, but again with the tool inclined;

Figure 5 is a perspective view of a practical apparatus showing the tool in the form of an insert;

Figure 6 is an enlarged front view of an insert; and

Figure 7 is a sectional view through the insert of

10 Figure 6 along the line VII-VII.

As has been mentioned above the invention consists in a cutting tool 10 having a part-elliptical symmetrical cutting edge such as is shown at 11. It has been determined that if such a tool is rotated about its point of symmetry 12 in either direction it will tend towards a radius and hence, in any given rotational position (or for any given angle of twist), will provide a cutting edge of a given radius at the point of the cutting edge 11 which engages a tube 13 passing below it.

For any given tool it has been found that rotation causes the ellipse to pass through a minimum radius and a particular maximum angle of twist is illustrated in Figure 1a. This angle of twist gives the minimum tube diameter which can be processed by that tool as shown in Figure 1b. The actual dimensions of the cutting edge 11 are determined as a function of the desired minimum tube diameter, the angle of twist and the cutting angle and clearance indicated in Figure 1b.

10

15

20

25

Conveniently the cutting tool 10 can be mounted in a tool holder 14 which is in turn mounted for rotation and axial displacement on a tool post slide 15. The tool holder should be arranged such that its axis of rotation 20 is orthogonal to the workpiece axis 21 and passes through the cutting edge 11 at the point of symmetry 12. This prevents the points 16 of the tool digging into the workpiece when in a rotated position.

However with a conventionally shaped tool such a position means that there is no clearance angle or rake angle and the tool would therefore be unsuitable for use on many materials. This can either be overcome by holding the tool at an angle as shown in Figures 3 and 4 or by shaping the tool 10 in such a way as to provide both the clearance angle and the rake angle on the tool. This can be clearly seen in Figure 7 where the tool is formed with a central well 23 to provide the rake angle and is inclined at 24 to provide the clearance angle. The former solution is easier to manufacture and is more compatible with existing systems. In either case the axis 20 passes through the point of symmetry 12.

Turning to Figure 5 a practical construction is generally indicated at 25. Here a tool holder 26 is supported on a conventional slide mechanism, generally indicated at 27 which allows for vertical and lateral positioning of the holder 26. The holder 26 comprises a cylindrical sleeve 28, which supports a barrel 29 having an upper annular flange 30 to lock it on the sleeve and a

10

15

20

25

frustoconical lower end 31. A bore 32 extends through the barrel to receive a tool support 32a which holds the tool 10 at its lower end. The support 32a can be locked into the barrel by means of screws 33 and the barrel can be locked into any selected rotational position by lock nut 34. For convenience the barrel is provided with a handle 35 so that the tool can be rotated into its selected operating position. It will be seen that slots 36 are provided in the sleeve 28 to allow this rotation.

In certain cases it may not be economic to retrofit such an arrangement and in this case a customer may be provided with a set of tool supports 32a or integral tools in which the cutting edge is effectively set at a particular angle of rotation. The appropriate tool for any shape can then be quickly selected and when used in this configuration the tool/insert will cover a greater range of tube sizes than currently available designs.

It will be understood that the new form of cutting tool will enable manufacturers to reduce their stock of tools and achieve better conformity between the effective cutting edge radius and the radius of the tube. In addition the scarf removing apparatus of which the tool forms a part can be adjusted simply by rotating the tool 10, over a range of radii, and this makes the apparatus particularly suitable for automatic operation by computer. Indeed the apparatus might include a number of tools with their given edges dimensioned to cover a wide range of radii and the control unit could simply lower the appropriate tool in a selected


rotational position for a particular size of tube to be processed at the moment. Where the ranges overlap between cutting tools the computer could select the appropriate tool depending on the relative wear that had taken place.


CLAIMS


- 1. A tool for removing burrs, scarf or the like from a circular cross-section body, the tool having a part elliptical symmetrical edge.
- 2. A tool as claimed in Claim 1, wherein the cutting edge is constituted by less than a quarter of an ellipse.
 - 3. A tool as claimed in Claim 1 or Claim 2 wherein the short axis of the ellipse extends through the centre line of the cutting edge.
- 10 4. A tool as claimed in Claim 1 in the form of an insert.
 - 5. A tool as claimed in Claim 4, wherein the insert is sintered.
- 6. A tool substantially as hereinbefore described with reference to the accompanying drawings.
 - 7. Apparatus for removing burrs, scarf or the like from a circular cross-section body comprising a tool having a part elliptical symmetrical cutting edge, means for supporting the body and the tool for relative movement for causing the cutting edge to cut over a longitudinal track on the body and means for mounting the tool for rotation about an axis orthogonal to the axis of the body, when located on the support means, and passing through the point of symmetry of the cutting edge.
- 25 8. Apparatus as claimed in Claim 1, wherein mounting means includes a tool holder.
 - 9. Apparatus as claimed in Claim 7 or Claim 8 further

comprising means for adjusting the rotational position of the tool, the angle of cut and/or the longitudinal position of the tool.


- 10. Apparatus as claimed in any one of Claims 7 to 9, wherein the tool is a tool as claimed in any one of Claims 1 to 6.
 - 11. Apparatus substantially as hereinbefore described with reference to the accompanying drawings.
- 12. A method of removing scarf ulitising the tool of any one of Claims 1 to 6 or the apparatus of Claims 7 to 11.
 - 13. A tube treated by a tool of Claims 1 to 6, the apparatus of Claims 7 to 11 or the method of Claim 12.









F163




MIST (6)









5/6








International Application No PCT/GB 90/01147

1. CLASSIFICATION OF SUBJECT MATTER (if several According to International Patent Classification (IPC) or to be IPC 5: B 23 D 79/02, 13/00, 2 II. FIELDS SEARCHED Minimum Do Classification System:	27/14 Documentation Searched 7	
IPC ⁵ : B 23 D 79/02, 13/00, 2 II. FIELDS SEARCHED Minimum Do Classification System:	27/14 Documentation Searched 7	
Minimum Do Classification System :		
Classification System:		
Classification System:		
.p.5	Classification Symbols	
15 a J	Classification Symbols	
B 23 D 79/00, 13	/00, 27/00	
Documentation Searched to the Extent that such Docu	other than Minimum Documentation iments are included in the Fields Searched	
III. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category • Citation of Document, 11 with Indication, when	re appropriate, of the relevant passages 12	Relevant to Claim No. 13
:		
A US, A, 3758740 (DUPY 11 September 197) 3 nes 42-54; figures	1,6,7
1,4,7,8	nes 42-54; rigures	
-, -, -, -, -		,
		•
A US, A, 3755884 (DUPY 4 September 1973		1,6,7
1,4,7,8	nes 40-52; figures	
A FR, A, 2475438 (META 14 August 1981 see page 2, line:		1,4-8
•		
	·	
!		
: :		
 Special categories of cited documents: 10 "A" document defining the general state of the art which is considered to be of particular relevance 	"T" later document published after to priority date and not in conflicted to understand the principle invention	
"E" earlier document but published on or after the Internation filing date "L" document which may throw doubts on priority claim(s) which is cited to establish the published of the stability that the stability the published on the stability of t	nal "X" document of particular relevan cannot be considered novel or involve an inventive step	ce; the claimed invention cannot be considered to
which is cited to establish the publication date of anoticitation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition other means	cannot be considered to involve or document is combined with one ments, such combination being	an inventive step when the
"P" document published prior to the international filing date taler than the priority date claimed V. CERTIFICATION	in the art. "&" document member of the same	
Date of the Actual Completion of the International Search	Date of Mellion - total to a series	
7th November 1990	Date of Mailing of this International Se	2 2. 11. 90
nternational Searching Authority EUROPEAN PATENT OFFICE	Signature of Authorized Officer M. Peß	M. PEIS

Form PCT/ISA/210 (second sheet) (January 1985)



ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 9001147 SA 39172

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 13/11/90

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 3758740	11-09-73	None	
US-A- 3755884	04-09-73	None	
FR-A- 2475438	14-08-81	None	

PCT





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

B23D 79/92, 13/00, B23B 27/14

(11) International Publication Number:

WO 91/01839

(43) International Publication Date:

21 February 1991 (21.02.91)

(21) International Application Number:

PCT/GB90/01147

A1

(22) International Filing Date:

25 July 1990 (25.07.90)

(30) Priority data:

8918174.7 9000677.6 9 August 1989 (09.08.89) GB 12 January 1990 (12.01.90) GB

GB

(71)(72) Applicants and Inventors: BARRACLOUGH, Keith, Sylvester [GB/GB]; Old Court Barn, West Mudford, Yeovil, Somerset BA21 5TJ (GB). CAREY, Ian [GB/GB]; The Dairy House, Charlton Horethorne, Sherborne, Dorset DT9 4NX (GB).

(74) Agents: DUNLOP, Brian, Kenneth, Charles et al.; Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB). (81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent)*, DK (European patent), ES (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), SU, US.

Published

With a revised version of the international search report.


(88) Date of publication of the revised version of the international search report:

15 October 1992 (15.10.92)

(54) Title: CUTTING TOOL

(57) Abstract

A cutting tool (10) has a part-elliptical symmetrical cutting edge (11). A holder (14) may be provided for allowing rotation of the tool (10) about an axis passing through its point of symmetry to provide a range of cutting radii. The application also includes the methods and apparatus utilising such tools.



• DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.


FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	A4-4
AU	Australia	PI	Finland	_	Madagascar
BB	Barbacios		-	ML	Mali
		FR	France	MN	Mongolia
BE	Bolgium	GA	Gabon	MR	Mauritania
BP	Burkina Faso	GB	United Kingdom	MW	Malawi
₽ G	Bulgaria	GN	Guinea		
BJ.	Benin			NL	Netherlands
_		GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD SD	Sudan
œ	Congo	KP	Democratic People's Republic		
CH	Switzerland			32	Sweden
CI	Côte d'Ivoire		of Korea	SN	Senegal
		KR	Republic of Korea	SU+	Soviet Union
СМ	Cameroon	니	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lunka	TG	
DE.	Germany	LU	Luxembourg		Togo
DK	Denmark	-	-	บร	United States of America
~~~	E-74 1111681 K	MC	Monaro		

+ It is not yet known for which States of the former Soviet Union any designation of the Soviet Union has effect.





International Application No PCT/GB 90/01147

ACTION OF SUBJECT MATTER 14 several	2181810021000 0 111	
According to international Patent Classification (IPC) or to cot	n National Cassification and ITC	
IPC ⁵ : B23D 79/92, 13/00, B23E	3 27/14	
d. FIELDS SEARCHED		
Minimum Dac	cumentation Searched 7	
Classification System .	Classification Symposis	
IPC ⁵ B23D 79/00, 13/00, 27/		
Documentation Searched of to the Extent that such Docum	ther than Minimum Documentation nents are included in the Field's Searched *	
III. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category •   Citation of Document, 11 with Indication, where	appropriate, of the relevant passages 12	Relevant to Claim No. 13
A US, A, 3758740 (DUPY) 11 September 1973 see column 3, lin 1,4,7,8	nes 42-54; figures	1,6,7
A US, A, 3755884 (DUPY) 4 September 1973 see column 3, lin 1,4,7,8		1,6,7
FR, A, 2475438 (METAL 14 August 1981 see page 2, lines		1,4-8
	·	
Social categories of cited documents: 18  "A" document defining the general state of the art which is not considered to be of particular relevance."  "E" acriier document but published on or after the international filing date.  "I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified).  "O" document referring to an oral disclosure, use, exhibition or other means.  "P" document published prior to the international filing date but later than the priority date claimed.  "V. CERTIFICATION  Date of the Actual Completion of the International Search.  "The November 1990.  Mernational Searching Authority	"X" document of perticular relevance cannot be considered novel or convolve an inventive attention of particular relevance cannot be considered to involve at document of particular relevance cannot be considered to involve at document is combined with one of ments, such combination being or in the art.  "E" document member of the same particular of Mailing of this international Sear 22.11.90	t with the application but or theory underlying the it the claimed invention annot be considered to it the claimed invention inventive step when the r more other such docu-vious to a person satiled tent family
EUROPEAN PATENT OFFICE	Signature of Authorized Officer H. Peß	M. PEIS

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 9001147 SA 39172

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 13/11/90

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 3758740	11-09-73	None	
US-A- 3755884	04-09-73	None	
FR-A- 2475438	14-08-81	None	

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:			
☐ BLACK BORDERS			
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES			
☐ FADED TEXT OR DRAWING			
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING			
☐ SKEWED/SLANTED IMAGES			
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS			
☐ GRAY SCALE DOCUMENTS			
LINES OR MARKS ON ORIGINAL DOCUMENT			
REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY			

# IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.